



MATERIAL SAFETY DATA SHEET

ALPINE GREEN CHOICE

ELITE OXYGEN DESTAINER

SECTION 1 – CHEMICAL PRODUCT & COMPANY IDENTIFICATION

PRODUCT NAME: Alpine Green Choice Elite Oxygen Destainer
GENERAL/GENERIC NAME:
PRODUCT USE: Oxygenated Laundry Whitener
EFFECTIVE DATE: October 6, 2011
VENDOR NAME AND ADDRESS: Alpine Specialty Chemicals Ltd.
24 Ronson Drive, Unit 16
Etobicoke, Ontario M9W 1B4
613-996-6666
24 HOUR EMERGENCY NO.

SECTION 2 – COMPOSITION / INFORMATION INGREDIENTS

| INGREDIENT | CAS.NO | %W/W | EXPOSURE LIMITS |
|-------------------|-----------|-------|--|
| Hydrogen Peroxide | 7722-84-1 | 20-60 | OSHA PEL: 1 ppm (1.4 mg/m3) TWA, NOISH IDLH: 75 ppm |

SECTION 3 – HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW: Hydrogen Peroxide aqueous solution is a clear, colourless liquid that is harmful if swallowed. This product is an Oxidizer that accelerates combustion of organic material (wood, paper, oil, and clothing). Elevated temperatures above (38oC) can increase the decomposition rate of the product. Material will decompose when exposed to heat, metals, alkalis, reducing agents or impurities and this will generate oxygen gas, steam and heat.

Route of Entry:

Skin Contact: Prolonged exposure causes skin irritation or burns.

Eye Contact: Severe irritation, redness, tearing and blurred vision. Stinging, burning, opaqueness of cornea. Prolonged contact may cause damage to eye tissue and possible blindness.

Inhalation: Irritating to nose, throat and respiratory tract. Severe overexposure could be fatal.

Inhalation, Chronic: Can cause nasal and respiratory irritation, dizziness, weakness, fatigue, nausea and headache.

Ingestion: Harmful if swallowed. Can burn mouth, throat and stomach. Oxygen gas in the stomach can cause swelling leading to severe injuries. Large exposure may be fatal

Effects of Acute Exposure: (see section 11 for Toxicological information).

SECTION 4 – FIRST AID

Eyes: Flush with running water for at least 15 minutes while holding eyelids open. Get medical attention.

Skin Contact: Flush contaminated skin with plenty of soap and water. Remove contaminated clothing. Launder contaminated clothing thoroughly before re-use. Seek medical attention if skin is burned or symptoms continue.

Inhalation: Remove victim to fresh air. Aid in breathing if necessary. If breathing stops, administer artificial respiration. Seek medical attention. Effects may be delayed for a few hours and aggravated by physical exertion.

Ingestion: Give plenty of water to drink to dilute stomach contents. **Do not induce vomiting.** Seek immediate medical attention.

Note to Physician: Risk of permanent corneal injury and possible blindness if splashed into eyes.

SECTION 5 – FIRE FIGHTING MEASURES

FLAMMABLE PROPERTIES

This product is not combustible, but a strong oxidizer. Mixtures with combustible or flammable materials may ignite easily, or may explode in contaminated, closed containers. Residual hydrogen peroxide that is dried on organic

MATERIAL SAFETY DATA SHEET

ALPINE GREEN CHOICE ELITE OXYGEN DESTAINER

materials such as wood, paper, fabrics, cotton, leather or other combustibles can cause the materials to ignite and result in a fire. **Auto Ignition Temperature:** Non flammable, but decomposes at approximately 38°C (100°F).

EXTINGUISHING MEDIA

Use water only!! Use large amounts of water and spray to cool containers. **Do Not** use dry chemicals, foam or a fire blanket. For large fires, flood fire area from a distance, do not flush to sewer unless concentration is 1% or less due to explosion hazard. Always stay away from the ends of tanks and wear self-contained breathing apparatus.
Oxidizer – keep away from flammable and combustible materials.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

Leak/Spill: Ventilate. Eliminate all sources of ignition. Wear full protective equipment including adequate respiratory protection. Review the safety procedures in case of explosion or fire, before proceeding in clean up. Comply with federal, provincial and municipal regulations. Do not use absorbents. Contain small spills using non-combustible material such as vermiculite, sand or earth. Flush combustible materials with large amounts of water.

SECTION 7 – HANDLING AND STORAGE

Handling Procedures: Avoid all skin contact. Ventilate adequately, otherwise wear an appropriate breathing apparatus. Avoid contact with eyes, skin or clothing. Never return unused peroxide to original container. Treat as flammable material; keep away from heat, sparks and open flames. Keep container closed when not in use.
Storage Procedures: Store in a cool, dry, well ventilated place away from other materials, Store in original, vented containers away from strong acids, strong oxidizing and reducing agents. Do not store in heat or direct sunlight. Store away from incompatible materials such as high pH material, metals, salts, organics, dust and dirt. Do not confine in un-vented vessels or between closed valves.

SECTION 8 – EXPOSURE CONTROLS

Exposure Guidelines: OSHA PEL: 1 ppm (1.4 mg/m³) TWA ACGIH TLV: 1ppm TWA NIOSH IDLH: 75 ppm

Engineering Controls: Use process enclosures, or local exhaust ventilation to keep airborne levels below recommended exposure limits. Emergency shower should be in close proximity. Eye wash facility should be close in proximity.

Personal Protective Equipment:

Gloves: Chemical resistant gloves. Butyl rubber gloves.

Respiratory: For vapour or mist concentration in excess of 10 ppm, a self-contained breathing apparatus (NIOSH/MSHA approved) should be used.

Eye/Face: Chemical goggles and face shield.

Footwear: Neoprene boots.

Clothing: Impermeable apron, PVC or rubber rain suit.

SECTION 9 – PHYSICAL PROPERTIES

Physical State: clear, colourless liquid

Odour Threshold: NA

Vapour Pressure (mmHg): (at 30 deg c)

Vapour Density (air = 1): 0.66 – 0.95

Boiling Point: 103°C – 120 °C

Solubility in Water (% w/w): 100%

Odour: Slightly sharp, pungent

Specific Gravity (water = 1): @35% 1.13

Viscosity: 1.05 – 1.21

Evaporation Rate: > 1

pH: Less than 2

Freezing Point: -17 °C to -56°C

SECTION 10 – STABILITY AND REACTIVITY

Hazardous Decomposition Products;

MATERIAL SAFETY DATA SHEET

ALPINE GREEN CHOICE ELITE OXYGEN DESTAINER

Hydrogen Peroxide decomposes on heating to product oxygen gas, steam and heat.

Stability

Yes: Stable when product is pure, stored under suitable conditions and temperature is less than 39°C.

No, which conditions: Stability is reduced when pH is above 4.0. Heat and contact with combustible materials.

Conditions to Avoid:

Reactivity Conditions: Avoid heating or mixing with organic materials, tissues. Containers can explode in fire.

Avoid contamination of any kind. Avoid contact with combustible material.

Hazardous Products of Decomposition: Oxygen, steam and heat.

Sensitivity to Static: May be sensitive.

Sensitivity to Impact: Protect against physical damage.

SECTION 11 – TOXICOLOGICAL INFORMATION

Harmful if swallowed, ingesting large amounts may be fatal.

Irritancy of Material: Extremely corrosive to all tissues, will cause irritation, burns.

Carcinogenicity of Material: Not listed

LD50 of Material, Species & Route: Oral: >2000 mg/kg (mouse). Vapour: 1437 ppm, 4 hours [rat].

SECTION 12 – ECOLOGICAL CONSIDERATION

Hydrogen Peroxide occurs naturally as a result of photochemical processes in living organisms. Product decomposes into water and oxygen. Harmful to aquatic organisms, especially algae. Freshwater algae are affected by hydrogen peroxide in concentrations of 2020 mg/L; while 1 mg/L affect certain marine algae.

SECTION 13 – DISPOSAL CONSIDERATIONS

Waste Disposal: In accordance with federal, provincial or local government requirements. Contact a waste disposal firm for advice. Empty containers should be rinsed with water prior to disposal. May create a fire or explosion hazard.

SECTION 14 – TRANSPORT INFORMATION

TDG Classification: Class 5.1 (8) Oxidizer, Corrosive UN 2014, PG II

Proper Shipping Name: Hydrogen Peroxide, Aqueous solution

SECTION 15 – REGULATORY INFORMATION

WHMIS Classification: Class C, D2B,E

On the DSL

SECTION 16 – OTHER INFORMATION

Prepared by: Lab Personnel

Phone: (416) 744-2120

Website: www.alpinechem.com

Disclaimer:

The information contained in this form is based on data from sources considered technically reliable and has been provided in good faith in accordance with the available material. It is provided as a service to the persons using the product but conditions of use and handling may involve other and additional consideration beyond our control. No warranty, expressed or implied, is made and we will not be liable for any damages, losses, injuries or consequential damages which may result from the use or reliance on any information in this form.