

# MATERIAL SAFETY DATA SHEET

## STEEL SHINE



### SECTION 1 – CHEMICAL PRODUCT & COMPANY IDENTIFICATION

PRODUCT NAME: Steel Shine  
GENERAL/GENERIC NAME:  
PRODUCT USE: Steel Cleaner  
EFFECTIVE DATE: October 6, 2011  
VENDOR NAME AND ADDRESS: Alpine Specialty Chemicals Ltd.  
24 Ronson Drive, Unit 16  
Etobicoke, Ontario M9W 1B4  
613-996-6666  
  
24 HOUR EMERGENCY NO.

### SECTION 2 – COMPOSITION / INFORMATION INGREDIENTS

Name CAS# % by Weight TLV/PEL LC50 LD50  
Isopropyl alcohol 67-63-0 1-5 TWA: 400 16970 ppm/4hrs. 3600 mg/kg  
CEIL: 500 ppm (Vapor Rat) (Oral Mouse)  
TWA: 900  
CEIL: 1225 mg/m<sup>3</sup>  
Normal heptane 000142825 10-30 TWA: 400 Not available Not available  
CEIL: 500 ppm  
TWA: 1600  
CEIL: 2000 mg/m<sup>3</sup>  
Liquefied petroleum gas 068476857 10-30 TWA: 1000 Not available Not available  
CEIL: 1250 ppm  
TWA: 1800  
CEIL: 2250 mg/m<sup>3</sup>

### SECTION 3 – HAZARDS IDENTIFICATION

**Route of Entry:**

**Skin Contact:** May cause irritation.

**Eye Contact:** May cause transient irritation.

**Inhalation:** Mist may cause irritation of the respiratory tract.

**Ingestion:** May cause irritation to digestive tract.

**Effects of Acute Exposure:** (see section 11 for Toxicological information).

### SECTION 4 – FIRST AID

**Eyes:** Flush with running water for at least 15 minutes while holding eyelids open. Get medical attention.

**Skin Contact:** Flush contaminated skin with plenty of soap and water. Remove contaminated clothing. Launder contaminated clothing thoroughly before re-use. Seek medical attention if skin is burned or symptoms continue.

**Inhalation:** Remove victim to fresh air. Aid in breathing if necessary. If breathing stops, administer artificial respiration. Seek medical attention. Effects may be delayed for a few hours and aggravated by physical exertion.

**Ingestion:** Give plenty of water to drink to dilute stomach contents. **Do not induce vomiting.** Seek immediate medical attention.

### SECTION 5 – FIRE FIGHTING MEASURES

FLAMMABILITY: Flammable Aerosol

AUTO-IGNITION TEMPERATURE: 215°C (419°F)

FIRE DEGRADATION PRODUCTS: These products are carbon oxides (CO, CO<sub>2</sub>) and other irritating gases.

FLASH POINTS: CLOSED CUP: -4°C (24.8°F) (TAGLIABUE)

FLAMMABLE LIMITS: LOWER: 1% UPPER: 12%

# MATERIAL SAFETY DATA SHEET

## STEEL SHINE

**FIRE EXTINGUISHING PROCEDURES:** Flammable liquid, insoluble in water. **SMALL FIRE** Use DRY chemicals, CO<sub>2</sub>, alcohol foam or water spray. **LARGE FIRE** Use water spray or fog. Cool containing vessels with water jet in order to prevent pressure build-up, autoignition or explosion. Avoid spreading burning liquid with water used to cool containers. Self-contained respiratory protection should be provided for firefighters.

**FLAMMABILITY:** Extremely flammable in presence of open flames and sparks, and heat. Very slightly to slightly flammable in presence of oxidizing materials.

The flashpoint of an aerosol by WHMIS definition is determined by its flame-extension or its flashback. The flame extension of this product is greater than 45 cm. Cdn. NFC. Level 3.

**RISKS OF EXPLOSION:** Risks of explosion of the product in presence of mechanical impact: Do not subject aerosol cans to impact. Risk of explosion of the product in the presence of static discharge: Aerosol spray may be sensitive to static discharge due to flammable concentrate and flammable propellant. Vapours of this product may form a flammable/explosive mixture when vapours present are between the lower (0.6%) and upper (19%) flammable limits and come into contact with open flames, sparks or static discharge Do not expose aerosol containers to open flames, heat or ignition sources.

### SECTION 6 – ACCIDENTAL RELEASE MEASURES

**Leak/Spill:** Contain spill; absorb onto inert material.

### SECTION 7 – HANDLING AND STORAGE

**Handling Procedures:** Avoid all skin contact. Ventilate adequately, otherwise wear an appropriate breathing apparatus. Avoid contact with eyes, skin or clothing. . Keep container closed when not in use.

**Storage Procedures:** Keep from freezing. Keep containers closed when not in use.

### SECTION 8 – EXPOSURE CONTROLS

**Engineering Controls:** Emergency shower should be in close proximity. Eye wash facility should be close in proximity.

**RESPIRATORY PROTECTION:**

**VENTILATION:** General ventilation adequate.

**PROTECTIVE GLOVES:** Gloves, impervious

**EYE PROTECTION:** Safety glasses

**OTHER PROTECTIVE MEASURES:** Apron and boots recommended under exceptional circumstances such as spill or for prolonged contact with bulk quantities.

### SECTION 9 – PHYSICAL PROPERTIES

**BOILING POINT:** 82.22°C(180°F) **VOLATILITY:** Not available

**VAPOR PRESSURE:** 15.5 mm of Hg (@ 20°C) **EVAPORATION RATE:** 4.5

**VAPOR DENSITY:** 2.68 (Air = 1) **pH(1% sol/water):** Neutral

**SOLUBILITY:** Insoluble in water **VISCOSITY:** Not available

**PHYSICAL STATE & COLOR:** Clear liquid, Mint odour **ODOUR THRESHOLD:** The highest known value

**SPECIFIC GRAVITY:** 0.745(Water = 1) is 49 ppm (Normal heptane)

### SECTION 10 – STABILITY AND REACTIVITY

**STABILITY:** Stable

**HAZARDOUS DECOMP. PRODUCTS:** Not available

**PRODUCTS OF DEGRADATION:** These products are carbon oxides (CO, CO<sub>2</sub>) and other irritating gases.

**REACTIVITY:** Avoid contact with strong oxidizing agents, strong acids and strong alkalies. Keep away from heat, sparks, open flame and all possible ignition sources.

### SECTION 11 – TOXICOLOGICAL INFORMATION

**ROUTES OF ENTRY:** Eye contact, Skin contact, Inhalation, Ingestion

# MATERIAL SAFETY DATA SHEET

## STEEL SHINE

### EFFECTS OF ACUTE EXPOSURE:

EYE: Contact may cause irritation, redness, tearing and itching.

SKIN CONTACT: Contact may cause defatting, drying and cracking of the skin.. Prolonged and repeated contact may lead to dermatitis.

INHALATION: Vapours may be irritating to nose, throat and respiratory tract. Excessive inhalation of vapors may cause nasal and respiratory irritation and Central Nervous System effects including dizziness, weakness, fatigue, nausea, headache and possible unconsciousness.

INGESTION: May cause gastrointestinal irritation, nausea, vomiting and diarrhea. Aspiration of material into the lungs can cause chemical pneumonitis, which can be fatal. Seek medical advise immediately and show the container or the label.

PRODUCT NAME: Steel Shine CODE: 6903 PAGE: 3

### EFFECTS OF CHRONIC EXPOSURE:

IRRITANCY: Hazardous by WHMIS criteria.

RESPIRATORY TRACT SENSITIZATION: No data available.

CARCINOGENIC EFFECTS: The ingredients of this product have been listed as carcinogens by the National Toxicology Program (NTP).

MUTAGENIC EFFECTS: No information available and no adverse effects are anticipated.

TERATOGENIC EFFECTS: No information available and no adverse effects are anticipated. Toxicity of the product to the reproductive system: Not available.

SYNERGISTIC MATERIALS: Not available.

### SECTION 12 – ECOLOGICAL CONSIDERATION

NA

### SECTION 13 – DISPOSAL CONSIDERATIONS

**Waste Disposal:** In accordance with federal, provincial or local government requirements.

### SECTION 14 – TRANSPORT INFORMATION

**TDG Classification:** Consumer Commodity

### SECTION 15 – REGULATORY INFORMATION

**WHMIS Classification:** Class A: Compressed gas. CODE: 6903

Class B-5: Flammable aerosol.

Class D-2B: Material causing other toxic effects (TOXIC).

### SECTION 16 – OTHER INFORMATION

Prepared by: Lab Personnel

Phone: (416) 744-2120

Website: [www.alpinechem.com](http://www.alpinechem.com)

#### **Disclaimer:**

The information contained in this form is based on data from sources considered technically reliable and has been provided in good faith in accordance with the available material. It is provided as a service to the persons using the product but conditions of use and handling may involve other and additional consideration beyond our control. No warranty, expressed or implied, is made and we will not be liable for any damages, losses, injuries or consequential damages which may result from the use or reliance on any information in this form.